

EXIT SIGN SHOP Photoluminescent Running Man Signs

2 Fc (22 lux) - 120 Minute Rated

Project Name: _____

Type of Project: _____

Prepared By: _____

Approved By: _____



Features

- Zero energy consumption - zero cost, green design
- Zero maintenance - no bulbs, no battery replacement
- Non-toxic, non-radioactive
- No disposal costs
- Designed for surface, flag, ceiling or conduit mounting
- Can be used for both high-level and low-level applications
- Easily movable if egress path changes
- Thin, low profile construction
- Consistent, uniform illumination, 50 ft rated visibility
- Recyclable
- LEED point contributor

Technical Information

Sizes available:
 RM with/ without Arrow Framing System (17.24 in x 10 in x 0.75 in) (43.8 cm x 25.4 cm x 1.9 cm)
RM without arrow is used over doors
RM with arrow is used to show the direction of egress
Background: Photoluminescent - Yellow
Tint Lettering/Image: Screen Printed Image
Flat Illumination: High Visibility Green
Visibility: 15.25 meters (50 feet) for a minimum of 120 minutes
Durability: Explosion-proof for areas requiring explosion-proof exit signage

Tests Passed:
 CAN/ULC S-572
Standard for Photoluminescent and Self Luminous Exit Signs and Path Marking Systems
 Meets National Building Code of Canada requirements
 Meets ISO 7010 Pictogram
 Rated for LED, Fluorescent, Metal Halide, Mercury Vapor

Life Expectancy
 25+ years

Power Requirements
 No additional electrical or mechanical source required

Installation
 Surface, flag, ceiling or stem mounted. Before installation it must be determined that there is a minimum of 2 Fc (22 lux) of light on face(s) of the sign at all times during building occupancy.



Model	RM-50R	RM-50RA	RM-50LA	RM-50SA
Product				
Description	No Arrow Single Sided	Right Facing Single Sided	Left Facing Single Sided	Double Sided